

Precision  
sound

# CC 550 IP

The Sennheiser CC 550 IP top-of-the-line headset offers precision sound to both ears for optimal understanding.

The highly durable construction is suited to all office and professional communication tasks.

This wideband headset delivers a more nuanced soundscape where voice transmission is perceived as warmer and more natural.

Use CC 550 IP for VoIP communication via softphones on PCs / MacBooks and IP desk phones.



**ActiveGard™**

Protecting your hearing

- **HD voice clarity** The CC 550 IP wideband headset delivers natural high-definition sound for superior voice clarity, accented speaker recognition, and reduced echo
- **Boosted productivity** The binaural headset blocks background noise, allowing total concentration for increased productivity
- **Superior fit** Independently adjustable dual-padded headband and ball-mounted speakers ensure a perfect fit
- **Precision positioning** 300° adjustable microphone boom for personalised mic placement, with Teflon®\* washer for optimal stability and durability
- **Optimum clarity** An ultra noise-cancelling microphone filters out ambient sounds for clearer speech
- **Protected hearing** ActiveGard™ technology protects against acoustic shock and sudden sound surges
- **Extra comfort** Generous headband padding and extra large ear pads evenly distribute pressure for longer lasting comfort – guaranteed



# Specifications

<b>Headset</b>	<b>CC 550 IP</b>
EAN No. (GTIN-13)	40 44155 04671 7
UPC No.	6 15104 17285 2
Art. No.	504017
<b>Technical data</b>	
Weight, headset	100 g
Weight, headset, cable and connector	110 g
Package dimensions	175 x 162 x 58 mm
Package weight	260 g
Units in distributor master carton	20
Weight master carton	6.4 kg
Dimensions master carton	370 x 330 x 380 mm
Wearing style	Headband, binaural (double sided)
<b>Microphone</b>	
	Ultra noise canceling
Frequency response	150 Hz – 6800 Hz
Distortion	Less than 1%
<b>Speaker</b>	
Impedance	~180 $\Omega$
Frequency response	150 Hz – 6800 Hz
Sound pressure	Max. 103 dB limited by ActiveGard™
All acoustic parts observe the TIA-920 wideband standards	
Ear cap size	Extra large $\phi$ 51 mm / 2.0 inches
Cable length	1 m / 3.3 ft Kevlar®* reinforced
Connector	Easy Disconnect

\* Kevlar® is a trademark of DuPont

<b>Accessories included</b>	
Acoustic foam ear pads	
Carry bag	
Clothing clip	
Coloured ID clips (3)	
Leatherette ear pads	
Microphone windscreen	