

# GAudio CM-II

## Ceiling Microphone Array



Product No: 20.YE.036

### Features

- **Omnidirectional pick-up microphone**  
Star array pick-up microphone, support dual mode (digital, analog) output
- **Intelligent voice tracking**  
Automatically focus on the current speaker without human intervention, clear sound and low noise.
- **Wide range pickup area**  
Pick up area covered 60 square meters, three times larger than the similar unidirectional products.
- **Perfect sound quality**  
Suspension ceiling features, optimized audio acquisition, transmit the sound authentically.
- Support 2 cascade ceiling mics (room size up to 100m<sup>2</sup>)

### Ceiling Microphone

Pickup radius	6 Meter
AEC , AGC, ANS	Support
Pickup Adapter	6 pin CANNON , used for connecting
System Indicator	Steady red: The system is starting Steady Green: Clock synchronization Green flashing: Normal Operation
Digital Interface	1*48V PoE power supply input, digital audio output 1*48V PoE power supply output, digital audio cascade
Audio output	RCA: Analog audio output
Audio Input	RCA: Analog audio input
Operating Temperature	-5°C ~ 40°C
Storage Temperature	-20°C ~ 60°C
Size	127mm x 110mm x 33mm



### Interface Box

Audio output	3.5mm audio interface
Mic Input	Mic-In
USB	1x USB-A
Connections	1x RS232 Port 1x Mic-In 1x AEC REF Interface 1x AEC OUT Interface 1x SPK 3.5mm Audio Interface 1X Ethernet Port 1x USB-A
System Indicator	Flashing slow indicated normal operation
Voltage	12V

